

The DigiPoS “Toccare” Bezel Free Touch Screen

A retail industry first, setting a new standard for display technology and quality.





Bezel Free Technology

The DigiPoS Toccare is a stylish touch screen with a quality finish, the perfect addition to the in-store experience.

A bezel free display designed with a glossy glass finish to the screen, providing outstanding image transmission. A stunning display that has to be seen to appreciate the quality of the design, build and finish.

Touch screen technology has become increasingly popular in retail as part of the point of sale system. The speed and ease of use increases operational efficiency providing a higher number of transactions, therefore improving the customer experience. Negating the need for a keyboard creates a cleaner environment while maximising counter space.

Retailers are continually looking for ways to enhance the customer experience in-store. The use of an interactive secondary display at the point of sale, information point, kiosk or providing an increased product range through in-store access to a webstore are all effective ways to achieve this.

The DigiPoS Toccare is an attractive touch screen providing the quality and durability required for a reliable customer facing display.

The aesthetic design of the bezel free display provides a front screen rating of IP64 and ensures a cleaner environment, a real advantage for a busy retail environment. High durability also allows for a high workload and harsh application.

The attractive glass like screen creates an eye-catching finish with high light transmission for perfect picture clarity and brilliant colours.

The Features

- Stylish bezel free design
- High durability and anti contamination for high workload and harsh application
- IP64 rating for the front surface
- Stylish glass finish screen
- High light transmission to provide perfect visual quality
- Windows Vista, XP and 7, Linux compatible
- Create intuitive applications (with Projected Capacitive Multi-Touch)
- Mounting holes on stand for security lock
- Worldwide main certification approvals: CE, FCC-B, TUV, UL, CUL and RoHS. Other approvals available upon request.

The Options

- Various mounting options – pole, wall and desk mount available
- Anti-glare and Anti-reflection coating – water resistant, dust and scratch proof
- Ergonomic MSR



Touch Technology

Multi-Touch Technology

The DigiPoS Toccare screen comes with multi-touch technology, also known as Projected Capacitive Touch. This enables the screen to detect more than one finger contact at once, allowing the user to manipulate the screen in a unique way. It also detects touch by a fingernail and even a gloved hand. Unlike the more traditional touch methods multi-touch technology doesn't wear out.

Multi-Touch technology provides an intuitive platform ideal to develop innovative applications enhancing the customer experience. It also allows the user to easily control the interface in a way that is familiar to most consumers.

- Drag to move the picture around
- Drag to zoom in and out
- Double click to enlarge
- Twist to rotate an image





The DigiPoS “Toccare” Bezel Free Touch Screen

Specifications

DIMENSIONS (INCL STAND)	364.4 (W) x 322.1 (H) x 206.21 (D) mm
POWER SUPPLY	Internal AC input power system, universal 100 ~ 240 Volts, DC 12V
POWER CONSUMPTION	Operating: 25W (typ.) / Sleep: 4W / Off: 2W
LCD SIZE / TYPE	15" (high gloss), 17", 19", and 22" diagonal TFT Active Matrix Panel
ACTIVE DISPLAY AREA	304 (H) x 228 (V) mm (15" version)
VESA MOUNT	75 mm
NET WEIGHT	13.5 lbs
PIXEL PITCH	0.297 (H) x 0.297 (V) mm
PANEL RESOLUTION	1024 x 768 (Max.)
DISPLAY MODE	VGA 720 x 400 (70Hz) VGA 640 x 480 (60/66/70/72/75Hz) SVGA 800 x 600 (60/70/72/75Hz) XGA 1024 x 768 (60/70/75Hz)
DISPLAY COLOUR	16.7M (6 bits + FRC)
CONTRAST RATIO	500:1
BRIGHTNESS	250 nits (typical)
RESPONSE TIME	8ms
VIEWING ANGLE — HORIZONTAL	Horizontal 140° (typical) Vertical 125° (typical)
VIDEO INPUT FORMAT	Video: RGB Analog 0.7V peak to peak
VIDEO SYNC FORMAT	Separated H&V Sync. / Composite Sync. / Sync-on Green
VIDEO INPUT FREQUENCY	31.47kHz ~ 60.02kHz / 56Hz ~ 75Hz (Horizontal / Vertical)
VIDEO SIGNAL INPUT	D-sub 15 pin Female (Analog)
AUDIO	1W Speaker / 2 Channels
PLUG & PLAY	DDC 2B Compatible
PERIPHERALS	3 Track MSR (Optional)
TOUCH TECHNOLOGY	Projected Capacitive Touch
TOUCH INTERFACE	USB
COMPLIANCE	TUV, CE, UL, CUL, FCC, RoHS, IP54

DigiPoS Store Solutions

760 Pacific Drive, Units 3 - 5, Oakville, Ontario L6L 6M5 | T: 1 866 847 2767 | E: sales@digipos.com
www.digipos.com

